



IMC/W2-dp Complete Meters 125 and 175 PSI MAOP

1. Select a Meter Size:

- | | | | | | |
|----------------------------------|-------------------------------|-------------------------------|-------------------------------|--------------------------------|----------------------------------|
| <input type="checkbox"/> 8C | <input type="checkbox"/> 11C | <input type="checkbox"/> 15C | <input type="checkbox"/> 2M | <input type="checkbox"/> 3M | |
| <input type="checkbox"/> 5M | <input type="checkbox"/> 7M | <input type="checkbox"/> 8.8M | <input type="checkbox"/> 11M | <input type="checkbox"/> 16M | |
| <input type="checkbox"/> 23M | <input type="checkbox"/> 38M | <input type="checkbox"/> 56M | <input type="checkbox"/> 102M | | |
| <input type="checkbox"/> G16 | <input type="checkbox"/> G25 | <input type="checkbox"/> G40 | <input type="checkbox"/> G65 | <input type="checkbox"/> G100 | <input type="checkbox"/> G160-3" |
| <input type="checkbox"/> G160-4" | <input type="checkbox"/> G250 | <input type="checkbox"/> G400 | <input type="checkbox"/> G650 | <input type="checkbox"/> G1000 | |

2. Select Meter Pressure Rating (psi)

- 125 (102M only) 175

3. Select Service type:

- Acetylene (all except 102M) Standard Special Service Meter (SSM)

4. Select Flange type:

- ANSI Flanged DIN (Not available on 11C or 102M)
 Nipped (8C-2M; G16-G40 only)

5. Select front panel Language:

- English Spanish

6. Select Corrector type:

- Pressure (P-only) Temperature (T-only) Pressure & Temperature (P&T)

If unit is T-only, proceed to Step 9

7. Select Pressure transducer type and the Pressure range if unit is P-only or P & T:

- | | | |
|------------------------------------|---|---|
| <input type="checkbox"/> Gauge: | <input type="checkbox"/> 30 psi (2 bar) | <input type="checkbox"/> 180 psi (12 bar) |
| <input type="checkbox"/> Absolute: | <input type="checkbox"/> 30 psi (2 bar) | <input type="checkbox"/> 180 psi (12 bar) |

8. Select Pressure Connection type:

External for ALL

If unit is P-Only, proceed to Step 10.

9. Select Temperature Probe if unit is T-only or P & T:

- Internal – Series B (8C-16M) External – Series B

For external temperature, select a probe & length of cable: (all cables are armored)

- | | | |
|---------------|---|--|
| 8-1/4" Probe: | <input type="checkbox"/> T1 (US 5-ft.) | <input type="checkbox"/> T2 (US 10-ft) |
| 2" Probe: | <input type="checkbox"/> T3 (Euro 5-ft) | <input type="checkbox"/> T4 (Euro 10-ft) |

NOTE: For meter sizes 102M; 23-56M; G400-G1000 choose T1 or T2 only.

10. Select Output Connection type and Cable Length if required:

- | | | |
|---|--|---|
| <input type="checkbox"/> Circular (single) | <input type="checkbox"/> Circular (dual) | <input type="checkbox"/> None (plug) |
| <input type="checkbox"/> Cable Gland (single) | <input type="checkbox"/> No Cable | <input type="checkbox"/> 5' <input type="checkbox"/> 10' <input type="checkbox"/> 30' <input type="checkbox"/> 50' |
| <input type="checkbox"/> Cable Gland (dual) | <input type="checkbox"/> No Cable | <input type="checkbox"/> 5' <input type="checkbox"/> 10' <input type="checkbox"/> 30' <input type="checkbox"/> 50' |
| <input type="checkbox"/> Conduit | <input type="checkbox"/> No Cable | <input type="checkbox"/> 5' <input type="checkbox"/> 10' <input type="checkbox"/> 30' <input type="checkbox"/> 50' <input type="checkbox"/> None (plug) |

NOTE: Dual Circular & Dual Cable Gland are not available on 23M-56M and G400-G1000 meters, or on any EP-ET unit.

11. Select Volume Input type:

- | | |
|-------------------------------------|---|
| <input type="checkbox"/> Mag Pickup | <input type="checkbox"/> Micro Generator™ |
|-------------------------------------|---|

12. Select Software Configuration type:

- | | |
|--|---|
| <input type="checkbox"/> Default Imperial | <input type="checkbox"/> Default Metric |
| <input type="checkbox"/> Custom (Consult factory to set up custom configuration) | |

**Roots Meters & Instruments
Dresser, Inc.**

16240 Port Northwest Drive
Houston, Texas 77041-2645 USA
Inside US Ph: 800.521.1114 Fax: 800.335.5224
Outside US Ph: 832.590.2303 Fax: 832.590.2494

