



IMCW2 with High Pressure Meters Configuration Worksheet

1. Select a Meter Size:

Imperial or Metric Meters

- | | | | | |
|---------------------------------|-------------------------------------|------------------------------------|-------------------------------------|-------------------------------------|
| <input type="checkbox"/> 1M300 | <input type="checkbox"/> 1M740 | <input type="checkbox"/> 1M740 BPV | <input type="checkbox"/> 1M1480 | <input type="checkbox"/> 1M1480 BPV |
| <input type="checkbox"/> 3M300 | <input type="checkbox"/> 3M740 | <input type="checkbox"/> 3M740 BPV | <input type="checkbox"/> 3M1480 | <input type="checkbox"/> 3M1480 BPV |
| <input type="checkbox"/> 5M1480 | <input type="checkbox"/> 5M1480 BPV | <input type="checkbox"/> 7M1480 | <input type="checkbox"/> 7M1480 BPV | <input type="checkbox"/> 11M1480 |

G-Series Meter Options

- | | | | | | |
|-----------------------------------|---------------------------------|-------------------------------------|------------------------------------|---------------------------------|-------------------------------------|
| <input type="checkbox"/> G16 as: | <input type="checkbox"/> 1M300 | <input type="checkbox"/> 1M740 | <input type="checkbox"/> 1M740 BPV | <input type="checkbox"/> 1M1480 | <input type="checkbox"/> 1M1480 BPV |
| <input type="checkbox"/> G25 as: | <input type="checkbox"/> 1M300 | <input type="checkbox"/> 1M740 | <input type="checkbox"/> 1M740 BPV | <input type="checkbox"/> 1M1480 | <input type="checkbox"/> 1M1480 BPV |
| <input type="checkbox"/> G40 as: | <input type="checkbox"/> 3M300 | <input type="checkbox"/> 1M740 | <input type="checkbox"/> 1M740 BPV | <input type="checkbox"/> 1M1480 | <input type="checkbox"/> 1M1480 BPV |
| <input type="checkbox"/> G65 as: | <input type="checkbox"/> 3M300 | <input type="checkbox"/> 3M740 | <input type="checkbox"/> 3M740 BPV | <input type="checkbox"/> 3M1480 | <input type="checkbox"/> 3M1480 BPV |
| <input type="checkbox"/> G100 as: | <input type="checkbox"/> 5M1480 | <input type="checkbox"/> 5M1480 BPV | | | |

2. Select front panel Language:

- English Spanish

3. Select Corrector type:

- Pressure (P-only) Temperature (T-only) Pressure & Temperature (P&T)

If unit is T-only, proceed to step 5

4. Select Pressure Transducer type and the Pressure range if unit is P-only or P & T:

- | | |
|------------------------------------|---|
| <input type="checkbox"/> Gauge: | <input type="checkbox"/> 350 psi (24 bar) <i>Use for 300 psi rated meters</i> |
| <input type="checkbox"/> Absolute: | <input type="checkbox"/> 435 psi (30 bar) <i>Use for 300 psi rated meters</i> |
| | <input type="checkbox"/> 1000psi (70 bar) <i>Use for 740 or 1480 psi rated meters</i> |

If unit is P-only, proceed to step 6

5. Select Temperature Probe if unit is T-only or P & T:

- | | | |
|---------------|---|--|
| 8-1/4" Probe: | <input type="checkbox"/> T1 (5 ft. Cable) | <input type="checkbox"/> T2 (10 ft Cable) |
| 2" Probe: | <input type="checkbox"/> T3 (5 ft. Cable) | <input type="checkbox"/> T4 (10 ft. Cable) |

NOTE: All cables are armored. US probe length is 8-1/4" length. Euro probe length is 2" length.

NOTE: If meter is one of the following sizes, choose T1 or T2 only. IM/3M740 & 1480; 5M/7M/11M1480.

6. Select Output Connection type and Cable Length if required:

- Circular
- Cable Gland
- Conduit
- None (plug)
- No Cable
- No Cable
- 5'
- 5'
- 30'
- 30'
- 50'
- 50
- None (plug)

Only available in Single output

7. Select Volume Input type:

- Mag Pickup
- Micro Generator™

8. Select Software Configuration type:

- Default Imperial
- Default Metric
- Custom (Consult factory to set up custom configuration)

**Roots Meters & Instruments
Dresser, Inc.**

16240 Port Northwest Drive
Houston, Texas 77041-2645 USA
Inside US Ph: 800.521.1114 Fax: 800.335.5224
Outside US Ph: 832.590.2303 Fax: 832.590.2494

