

Table 1 - Measurement Ranges and Pulse Data

| G-ratng | Comparable U.S. Rating | Size | | Q-max Rated Capacity m ³ /h | Range Availability | 2 x Low Frequency Pulses (pulses/m ³) |
|---------|------------------------|-----------|---------|--|--------------------|---|
| | | Inch | mm | | | |
| G-16 | 2-M | 1.5" | 40 | 25 | 1:80 | 10 |
| G-25 | 2-M | 1.5" | 40 | 40 | 1:100 | 10 |
| G-40 | 2-M | 1.5" & 2" | 40 & 50 | 65 | 1:100 | 10 |
| G-65 | 3-M | 2" | 50 | 100 | 1:160 | 10 |
| G-100 | 7-M/11-M | 3" | 80 | 160 | 1:160 | 1 |
| G-160T | 7-M/11-M | 3" | 80 | 250 | 1:160 | 1 |
| G-160 | 7-M/11-M | 3" | 80 | 250 | 1:160 | 1 |
| G-250 | 16-M | 4" | 100 | 400 | 1:160 | 1 |
| G-400T | 23-M | 4" | 100 | 650 | 1:160 | 1 |
| G-400T | 23-M | 6" | 150 | 650 | 1:160 | 1 |
| G-650T | 38-M | 6" | 150 | 1000 | 1:160 | 1 |

Table 2 - Dimensions and Weights

| G-ratng | Number of Bolts | Size | | Overall Flange to Flange Dimensions | Height & Depth | | Overall Weight in Kg Approx Values |
|---------|-----------------|------|-----|-------------------------------------|----------------|-----|------------------------------------|
| | | Inch | mm | | mm | mm | |
| G-16 | N.A. | 1.5" | 40 | 121 - without Flanges | 130 | 200 | 5 |
| G-25 | N.A. | 1.5" | 40 | 121 - without Flanges | 130 | 220 | 5 |
| G-40 | 4 | 1.5" | 40 | 171 | 180 | 220 | 10 |
| G-65 | 4 | 2" | 50 | 171 | 180 | 220 | 10 |
| G-100 | 4/8 | 3" | 80 | 171 | 200 | 280 | 13 |
| G-160T | 4/8 | 3" | 80 | 171 | 200 | 350 | 21 |
| G-160 | 4/8 | 3" | 80 | 241 | 225 | 315 | 27 |
| G-250 | 8 | 4" | 100 | 241 | 225 | 400 | 30 |
| G-400T | 8 | 4" | 100 | 241 | 225 | 510 | 43 |
| G-400T | 8 | 6" | 150 | 241 | 285 | 510 | 50 |
| G-650T | 8 | 6" | 150 | 241 | 285 | 680 | 61 |